

TOP AIR® 3-POINT SPRAYERS

Top Air® 300-gallon 3-point sprayers provide exceptional maneuverability and unmatched performance for any size operation.

300 GALLON





3-POINT SPRAYER FEATURES AND BENEFITS

- Equipped with a 300-gallon capacity tank, hydraulic pump and manual agitation control.
- Available with a 45' manual, 45' or 60' hydraulic cross-fold, self-leveling boom with three-section boom shutoff.
- Outer wing breakaway quickly returns to spraying position should it come into contact with an obstruction.
- Compact design and fold for narrow transport width and height, along with standard parking stands for easy storage.
- Slow moving vehicle sign and reflective striping for safer road travel.
- Optional fence-row nozzle kit for operator convenience.
- Nozzle spacing available in 15" or 20" to meet the needs of different operations.
- Hydraulic vertical height control on the 45' and 60' hydraulic cross-fold booms allows for easier spraying of taller crops.
- Frame and boom feature high-quality finish for enhanced corrosion resistance.
- Optional foam marker gives you precise spraying, pass after pass.

Stop at your local Top Air dealer today or visit us online at topairequip.com and check out the Top Air 3-point sprayer!



Unverferth
Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853
419-532-3121 • unverferth.com

As we continually strive to improve our products, all specifications contained herein are subject to change without notice or obligation.



®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co. Inc., Kalida, O.H.

© 2014

TA3PT300414030M3

SPECIFICATIONS

| | 45' MANUAL-FOLD BOOM | 45' HYDRAULIC CROSS-FOLD BOOM | 60' HYDRAULIC CROSS-FOLD BOOM |
|------------------|-------------------------|----------------------------------|----------------------------------|
| Transport Height | 7' 7" | 10' | 10' |
| Transport Width | 8' | 12' | 13' |
| Length Added | 6' | 7' 1" | 7' 1" |



Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. We support the efforts of Farm Safety 4 Just Kids and all organizations that promote farm safety.

TOP AIR[®] **3-POINT SPRAYER**

Only the Top Air[®] 600-gallon 3-point sprayer combines the advantages of big-boom performance with exceptional maneuverability for greater operator convenience and precision placement.

600-GALLON





600-GALLON 3-POINT SPRAYER FEATURES AND BENEFITS

- 600-gallon capacity solution tank and a 50-gallon rinse tank.
- Hydraulic-driven centrifugal pump and electric agitation control.
- Hydraulic bi-fold, self-leveling booms in 80' three-section or 90' three- or six-section boom shutoffs
- Outer wing breakaway quickly returns to spraying position should it come into contact with an obstruction.
- Compact design and fold for narrow transport width and height, along with standard parking stands for easy storage.
- Standard Raven 4400 controller for complete and easy rate control.
- Nozzle spacing available in 15" or 20" to meet the needs of different operations.
- Parallel-lift boom system with 57" vertical-height control for uniform boom lifting for easier spraying of taller crops
- Frame and boom feature high-quality finish for enhanced corrosion resistance.

Options

- Foam marker gives you precise spraying, pass after pass
- Auto-boom height control, sonar or wheel sensors (dealer installed only)
- Chemical inductor for quick and easy introduction of chemicals into the tank
- Fence-row nozzle kit for easily spraying along the end rows
- Rear hitch for pulling nurse tanks behind sprayer
- FLO-BAK® ball valves for instant shut-off and chemical savings



See your local Top Air® dealer today,
or visit us online at topairequip.com and
check out the Top Air 3-point sprayer line!

Unverferth
Manufacturing Company, Inc.

P.O. Box 357 Kalida, Ohio 45853
419-532-3121 unverferth.com

®™ Trademarks, registered or applied for,
of Unverferth Manufacturing Co., Inc., Kalida, OH



© 2013

TA3PT311210M3

SPECIFICATIONS*

| | 600-GALLON |
|---------------------|------------------------|
| Transport Height | 11' 8" |
| Transport Width | 16' 9" |
| Length Added | 6' 1" |
| Tank Capacity | 600 gallons |
| Boom Type | 80' or 90' bi-fold |
| Empty Weight | 5,000 lbs. |
| Coverage (90' boom) | 65.5 acres/hr @ 12 mph |

*As we continually strive to improve our products, all specifications contained herein are subject to change without notice or obligation.



Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. We support the efforts of Farm Safety 4 Just Kids and all organizations that promote farm safety.