



A High-Capacity Ride **FOR HIGH-QUALITY GRAIN**

Now you can transport grain to the bin site or elevator in town with fewer trips than ever. The 750-bushel capacity Unverferth® model 730 grain wagons are specifically designed to be pulled in tandem fully loaded and feature easy connections for linking multiple units.

The newly designed unloading chute also features a self-locking mechanism for labor-saving positioning for transport. The chute is equipped with a center-dump deflector for pit unloading and is height adjustable from 15" to 18". There's also a metering door which makes it easy for pulling grain samples.

Unverferth Model 730 Grain Wagon: A High-Quality Ride For High-Quality Grain

Standard features:

- Steep-sloped, graphite-coated sidewalls and large, 60" door opening for fast and complete unloading of up to 750 bushels in 110 seconds
- The unloading door's rack and pinion mechanism with gear reduction and grain sampling door allows for easy opening, even when the box is full
- Patented UltraSteer® chassis allows the wagon to be turned in a 40 percent tighter radius than traditional wagons
- Torsion bar suspension and extra-wide 42" runner spacings keep the wagon level and stable, even when traveling against rows
- Heavy-duty spindles and hubs for years of dependable service
- High-intensity halogen light positioned above the unloading door for making nighttime unloading as bright as high noon
- All wiring is mesh-coated and routed through conduit for extra protection and longer life
- 4-wheel, surge-activated brakes and heavy-duty safety chain for safer transport
- ASAE-approved, high-intensity flashing amber and red taillights, SMV emblem, 7-pin electric receptacle, rear hitch and welded-steel safety chain connector for easier, safer and more convenient multiple-unit towing
- Front viewing ladder and front, side and rear viewing windows for easy load checking
- Full primer basecoat and available in choice of tractor red or green high-gloss top coat for a car-like finish; all exposed seams silicone-sealed to resist corrosion
- Left-side unloading

Accessories:

- Self-locking, easy-to-operate rollover tarp for protecting load contents
- Molded plastic fenders with mud flaps to protect wagon finish and side-marker lights for improved nighttime visibility
- Right-side unloading

See your nearest Unverferth dealer today for complete details about the model 730 and the complete line of Unverferth grain wagons, check our website at umequip.com or call 1-800-322-6301.



Spring-lift-assist tongue



Innovative latching chute design

Model 730* specifications

Capacity**	750 bushels
Length	11'7"
Width	9'6"
Height	10'8"
Height with tarp	11'4"
Front/rear slope	39°
Back slope	37°
Door width	60"
Chute height	15" to 18"
Hub size	10-bolt
Wheel size	445/65R22.5
Wheel base	12'1"
Track width	7'5"
Turning radius (ID)	12'
Approx. empty weight	7,950 lbs.

*Please check local weight and towing regulations when towing the model 730 singly or in tandem

**Capacities measured with #2 corn at 15% moisture (56 lb. test weight)

Due to continuing improvements in the design and manufacture of all Unverferth products, all specifications contained herein are subject to change without notice.

Unverferth
Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853
(419) 532-3121 • FAX (419) 532-2468
unverferth.com

1-800-322-6301

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2013 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH.

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada.



UGW3162800M5