

**Unverferth**® Seedbed Tillage

**Maximus**® Disk



## **Tillage versatility** *at its greatest*

*The word maximus is Latin for “the greatest”, and that’s why it was chosen for this unique disk. For maximum disk tillage in a variety of applications, including between orchard and vineyard rows, look to the Unverferth Maximus® disk.*

*Model 100*

# Maximus® Disk Model 100



Tool-free, cutting-angle adjustability



Blade scraper kit/triple-lip sealed bearings

1. Reversible, self-aligning hitch can be easily positioned to either the front or rear of the implement for greater versatility.
2. Both front and rear gangs feature tool-free, gang-positioning adjustability from the traditional X-shape to a diamond-shape to match the desired level of tillage aggressiveness and width.
3. Aggressively tills and penetrates soil between rows up to six inches deep for effective, efficient weed control and soil leveling.
4. Its heavy-duty 3"x3" and 2"x6" welded steel frame provides durability and consistent, uniform penetration.
5. Blades feature 9" spacings and are mounted on a 13/4" round shaft for maximum durability. Triple-lipped greaseable bearings with 10,800 lbs. of dynamic-load rating provide long life.
6. One gang features notched 24" disk blades and the other features smooth 24" blades.
7. Tool-free adjustable working width in 2-inch increments.
8. Powder-coat finish of implement red to resist corrosion.
9. Options:
  - a furrowing shovel can be positioned between the front gangs or the middle of the disk, and it's depth-adjustable with a simple pin setting
  - aggressive Rolling Harrow® basket, with angled, high-carbon-steel scalloped blades, finishes off weeds by knocking soil from roots and leaving them on the surface to wilt and die
  - blade scraper kit eliminates buildup, even in wet, sticky soil
  - blade shields deflect soil downward
  - width-adjustable side shields protect fragile fruit trees and grape vines
  - bolt-on blade extensions expand working width by 1'5"
  - hitch extension kit provides 4" of added clearance for most aggressive settings disks

## Model 100 specifications

Frame	Working Width	Gang	Blade Number	Approx. Weight (lbs.)
6'	5'3"-6'2"	Add-a-Blade Capable	8-Front 8-Rear	1,805
7'	5'3"-7'2"	Add-a-Blade Capable	8-Front 8-Rear	1,805
7'	6'8"-8'7"	Fixed	10-Front 10 Rear	2,400

## Common specifications

Horsepower required	5 h.p. to 9 h.p. per foot
Blade specifications	24" x 1/4"
Cutting-angle adjustability	11 positions / +29° to -29°
Working depth	up to 6"
Hitch types	category 1 std., 2 std. and quick, 3 std. and narrow quick hitch



**See your nearest Unverferth dealer or [umequip.com](http://umequip.com) for complete details on the Maximus disk and the complete line of Unverferth tillage equipment. Our roots are deep in tillage.**

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.

**Unverferth**  
Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853  
(419) 532-3121  
[unverferth.com](http://unverferth.com)

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2016 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon, Ontario and Saskatchewan, Canada



UMMD6120205M2