



## INTRODUCING THE ALL-NEW 20-SERIES LINEUP

MODELS 6120, 5120, 4120 & 3120

The all-new Blu-Jet 20-Series lineup of anhydrous ammonia (NH<sub>3</sub>) applicators offers the widest range of sizes and row spacings to fit any operation's needs. In addition, a wide selection of options and accessories allow you to customize the row unit, plumbing and distribution system, so you're guaranteed to receive a field-ready unit that matches your requirements, straight from the factory.

### MODELS AND OFFERINGS

**Model 6120** ranges in size from 18-row 30" up to 25-row 30" and is the heaviest-built NH<sub>3</sub> applicator on the market. 6120 features wing flex on the primary and secondary wings to follow varying ground contours and comes standard with 22.5" main frame tires but can be upgraded to 38" tractor dual tires on the main frame.

**Model 5120** is available in sizes from 12-row 30" up to 21-row 30" and is the perfect fit for large farming operations looking to take control of their NH<sub>3</sub> application program. This model features wing flex on the primary wing to follow subtle field contours and comes standard with 22.5" main frame truck tires but can be upgraded to 34" single tractor tires on the main frame.

**Model 4120** offers toolbar sizes ranging from 11-row 30" up to 17-row 30" for mid-acreage farming operations looking for a price-competitive NH<sub>3</sub> applicator. Standard wing flex is present on the primary wings for following field contours, and the model has standard 15" dual implement tires on the main frame but can be upgraded to a walking tandem axle frame in lieu of the duals.

**Model 3120** is a 3-point model that is available in sizes ranging from 11-row 30" up to 17-row 30". Model 3120 is standard with a CAT3 and 3N 3-point hitch, primary wing flex, and 4" x 6" mainframe for maximum durability.

# NH3 FEATURES & ACCESSORIES

## PULL-TYPE FRAME & TOOLBAR

Pull-type models 6120 and 5120 are standard with a new heavy-duty 8"x4" A-frame tongue design, single-point manual depth control adjustment, and a CAT4 ball swivel and clevis hitch.

Model 4120 features a standard 6"x4" A-frame tongue with a CAT3 hitch on models up to 15 rows and a CAT4 hitch on 17-row models.

Models 6120 and 5120 feature a heavy-duty 6"x6" toolbar mainframe with 54" of toolbar rank for maximum residue flow.

Model 4120 features a 4"x6" toolbar mainframe with 38" of toolbar rank.

## ROW UNIT DESIGN

New lead coulter design features a horizontal spring with 1,500 pounds of down pressure for consistent soil penetration, 4-bolt hubs, 20" fluted blades and 30° of total swivel to clear a path for the NH3 shank.

Edgebent shanks are 1.25" wide and feature a twin spring-cushioned design for reliable and consistent working depth. For the most consistent working depth in heavy soils, MaxPac shank mounts are available in lieu of the spring cushions and feature 790 pounds of trip force.

Standard 0.75" NH3 mole knives with many sizes and styles are available as optional accessories.

New SealPro II closing coulters feature tool-free angle adjustability with automatic locking positions, notched blades, independent movement and 4-bolt tapered bearings for long-term, trouble-free use. Optional down pressure springs can be added to the closing coulters for tougher soils.

## NH3 DISTRIBUTION

A new standard Ag Leader ISOBUS controller allows the operator to control all NH3 distribution functions from the tractor's VT screen and includes a switch box for convenient on/off operation and manual section control.

A standard Raven vortex cooler with 50 gallons per minute of flow and 1.5" single fast valve is available. Optional single or dual Continental coolers are available.

Two-section plumbing is standard with John Blue impellicones and Raven section shutoff valves. Depending on model and size, up to 6-section options are available with John Blue impellicones or Continental A-360 manifolds.

The innovative rear nurse tank hitch features tool-free adjustability with a telescoping design for quick and safer hookup. The single SuperShooter III nurse tank with 1.25" plumbing connection features a splash guard and quick disconnect for the safest operation.

## OPTIONS & ACCESSORIES

Models 6120 and 5120 can be equipped with a new larger capacity 200-gallon direct injection nitrogen stabilizer system that operates through the ISOBUS system.

Optional dual nurse tank hitch add-on kit adds two hitches in addition to the standard hitch in the center for towing two nurse tanks in the field or one nurse tank down the road.

Additional options and accessories include 1.5" dual valves in lieu of the single fast valve, double SuperShooter III nurse tank plumbing connection, 20" lead vortex coulters blades, 17" wavy closing coulters blades and implement height switch for automatically shutting off the NH3 flow when the machine is raised.

▶ Visit [BluJetEquip.com](http://BluJetEquip.com) or see your nearest dealer to discover why Blu-Jet products are **Leaders in the Field**.



MODEL 6120

8" x 4" Tongue & Optional  
200 Gallon Injection Kit



Tool-Free Row Closer Angle  
Adjustment



Telescoping Rear Nurse  
Tank Hitch