



DESIGNED TO PERFORM
BUILT TO LAST

ALL-NEW 2598 WITH STEERABLE TANDEM

AVALANCHE® DUAL-AUGER GRAIN CARTS

New!

**FOR LONGER HAULS
& A SMOOTH RIDE.**



STEERABLE TANDEM UNDERCARRIAGE
NEW FOR 2026



The Brent 2598 Avalanche® dual-auger grain cart features a 2,500 bushel hopper capacity and can now be equipped with steerable tandem wheels and tires to meet operator preferences.

The 2598 features a 1,000 bushel per minute unloading speed so you can get back to the combine quicker, and convenient unloading features such as a pivoting vertical auger and standard 4-way downspout which makes loading trucks quick and easy. The new self-steering tandem wheel and tire undercarriage features Para-Link suspension from front to rear for ideal cart control. When you're ready for the best, you're ready for a Brent 2598 Avalanche grain cart with steerable tandem undercarriage.

GRAIN HANDLING

UNVERFERTH MANUFACTURING CO., INC.
P.O. BOX 357, KALIDA, OH 45853

PERFORMANCE, REDEFINED.

2598 GRAIN CART FEATURES

- Model 2598 features a 2,500 bushel hopper capacity and is available in tractor red, green or the exclusive metallic black paint.
- Rear access door and ergonomic ladder permits easy access inside the hopper.
- Standard roll-tarp protects the harvested crop and a 520 scale package is included for easy weight recording and verification.
- The 2598 Avalanche features a dual-auger design combining a 20" horizontal floor auger that feeds the 24" vertical auger for a low-profile design and unloading speeds up to 1,000 bushels per minute.
- The pivoting vertical unloading auger allows the operator to raise the auger when pulling up to a truck and lower it into position when unloading.
- The standard 4-way directional downspout allows the operator to re-direct grain with limited tractor movement to easily top off trucks.
- Depending on operator preference, the 2598 can be ordered with a traditional left-hand unloading auger or a right-hand unloading configuration.
- Exclusively designed max-edge auger flighting combines 3/8" thick flighting with 1/4" thick AR400 wear strips in high volume areas to maximize life.
- Rubber-cushioned tongue suspension provides a smoother ride through the field and standard hydraulic jack makes hitching the cart quick and easy.
- The exclusive drivetrain design combines a field-proven belt drive for the horizontal auger with a heavy-duty 90° gearbox for the vertical unloading auger.
- The patented steerable tandem wheel and tire undercarriage automatically turns in unison with the tractor and features oscillation, so all four tires stay on the ground through uneven terrain for maximum flotation.
 - The heavy-duty undercarriage features 6" spindles and 12-bolt hubs with IF1100/50 x R42 tires.
 - The Para-Link suspension from front to rear ensures ideal cart control and features hydraulic cushioning for a smoother ride.
 - For easy backing and tight turns, the hydraulic override can be actuated by the operator and includes an incremental gauge to determine wheel direction
- Options for the 2598 grain cart include hydraulic disc brakes, the UHarvest® Pro data management system, 275-gallon water delivery system, 5-function joystick controller, electric roll tarp operation, remote scale display with recessed area in the side of the hopper and more.



REAR ACCESS DOOR



4-WAY DIRECTIONAL DOWNSPOUT



WATER DELIVERY SYSTEM



RECESSED SCALE DISPLAY

SPECIFICATIONS		
		2598
CAPACITY (BUSHEL)*		2,500
ENGINE HP		4WD-500+
LOADED TONGUE WEIGHT (LBS.)		6,700
EMPTY TONGUE WEIGHT (LBS.)		4,800
AUGER DIAMETER		24"/20"
UNLOADING SPEED (BUSHEL/MIN.)		1,000
FLIGHTING THICKNESS		3/8" with 1/4" AR400
HYDRAULIC REMOTES REQUIRED		6
HOPPER LENGTH		33'
HOPPER WIDTH		13' 10"
AUGER SIDE REACH MAX.	MEASURED TO INSIDE EDGE OF RUBBER SPOUT	10' 9"
AUGER SIDE REACH MIN.		6' 1"
OVERALL TRANSPORT LENGTH		42' 6"
HITCH TO CENTER OF AXLE		29' 6"
MEASURED UNDERCARRIAGE		IF1100/50R42
EMPTY WEIGHT (LBS.)		41,000
HITCH HEIGHT		1' 6"
HOPPER HEIGHT LOW SIDE		11' 2"
HOPPER HEIGHT HIGH SIDE		12' 2"
AUGER HEIGHT WITH SPOUT STRAIGHT DOWN		16' 3" - 9' 10"
HEIGHT TO TOP OF AUGER IN UNLOAD POSITION		21' 3" - 15' 4"
WIDTH OUTSIDE OF TIRES		15' 4"
CENTER OF TIRE TO CENTER OF TIRE		11' 6"
UNDER FRAME CLEARANCE		1' 6"

*Bushel capacities and unloading speeds are measured with #2 corn at 15% moisture (56-pound test weight).

Due to continuing improvements in the design and manufacture of Unverferth Mfg. products, all specifications contained herein are subject to change without notice.

For more information or to see the full lineup of 98-Series Avalanche Dual-Auger grain carts, see your nearest dealer today or visit BrentEquip.com.

Unverferth
Manufacturing Company, Inc.

© 2025 Unverferth Manufacturing Co., Inc.
®/™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH

UNVERFERTH MFG. CO., INC.
P.O. BOX 357, KALIDA, OH 45853, USA • UNVERFERTH.COM • 419.532.3121

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Texas, Washington and Ontario and Saskatchewan, Canada