



Track TILLr



MODEL 500

Don't Just Fill Your Tracks, TILL Them

When it comes to tillage, the Orthman spirit of innovation continues to shine with the model 500 Track TILLr. Its exclusive design eclipses conventional pivot track fillers by leaving a planter-ready finish rather than simply covering the pivot track. The soil nearest the track is pulled in with the dual notched blades followed by a mid-wheel packer for pre-leveling and then hydraulically adjustable, tapered rear disc gangs to complete the leveling. Then, the standard double rolling baskets smooth and condition the surface for a ready-to-plant seedbed.

A TOUGH ACT TO FOLLOW

RESIDUE MANAGEMENT

Track TILLr

TILLAGE TOOL

The Track TILLr 500 is proven to level soil nearly three times flatter than conventional track fillers with standard rolling levelers. Here's how it works:

1. The front-mounted, width- and depth-adjustable guide wheel centers the machine in the pivot track to accurately control the tillage depth. The recessed bearing design reduces residue wrapping and protects the four heavy-duty bearings for years of reliability.
2. The targeted tillage process begins with a pair of massive 22" notched disc blades that break up the toughest sidewall compaction and fill the bottom of the track rut with more soil and less residue than traditional track fillers. The width-adjustable discs are mounted on large tapered roller bearings to ensure season after season of trouble-free service.
3. The center-mounted 10"-wide packer wheel features cleated drive lugs to propel it through the toughest soils. To optimize the firmness of the soil, the packer features 4 1/2" of height adjustment along with up to 1,500 pounds of down pressure adjustability.
4. Tool-free angle-adjustable disc gangs with concave blades that decrease in diameter from 22" down to 16" on the outside to feather the soil and residue out to 100" wide for a smooth finish.
5. Standard spring-cushioned dual rolling baskets with angled blades provide added soil leveling for a planter-ready finish. Down pressure is easily adjusted to provide ideal leveling from field to field and match soil conditions.



ADJUSTABLE GUIDE WHEEL



22" NOTCHED DISC BLADES




10"-WIDE PACKER



ADJUSTABLE DISC GANGS



DUAL REAR ROLLING BASKETS



Options include

- On-the-go hydraulic down pressure adjustability of the rolling baskets
- Disc blade scrapers for wet, compacted soils

Track TILLr 500 Specifications

REQUIRES 100 HP				
DISC GANG BLADES				
Inner to Outer — Each Side	22"	18"	16"	16"
Working Width	8'6"			
Overall Width	8'8"			
Overall Length	10'			
Approx. Weight	2,750 lbs.			

▶ STOP BY YOUR ORTHMAN TRACK TILLr DEALER TODAY OR VISIT ORTHMANEQUIP.COM TO LEARN HOW YOU CAN ACHIEVE UNMATCHED SEEDBEDS IN TIME FOR THE NEXT PLANTING SEASON.

Unverferth
Manufacturing Company, Inc.

P.O. Box 357 | Kalida, OH 45853 | 419-532-3121
Unverferth.com

©™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Texas, Washington, Ontario and Saskatchewan, Canada

© 2024 Unverferth Manufacturing Co., Inc. Printed in USA

OTRACK425120005M2