



PARKER® GRAIN CART MODEL 1648

Workhorse power plus racehorse speed — large 1,600-bushel capacity with incredible unloading speed for unmatched harvest efficiency!



Parker® Grain Cart Model 1648: Workhorse power with racehorse speed!

Combine the workhorse power (1,600-bushel capacity) of the Parker grain cart model 1648 with its racehorse speed (unloading rate of 840 bushels per minute) and you'll get quickly back to the field to keep the combine moving.

- Dual-auger unloading system features 20"-diameter floor auger and 22"-diameter vertical auger
- Hydraulic spout control for easier unloading
- Hinged clean-out doors on both floor and vertical augers for easy maintenance
- Tubular steel construction for optimal support and durability
- Convenient storage rack for electrical connector and color-coded, labeled hydraulic hoses for easy connection
- LED lighting, reflectors and transport chain for safer transport
- Silicone-sealed seams resist corrosion
- Available in choice of tractor red or green



The upper portion of the unloading auger rests on a convenient flip-up stand for quick folding and unfolding during field operation. The stand flips down and the upper auger then rests securely against the fixed, lower portion of the unloading auger for safer road transport and space-efficient storage.



A rugged drivetrain design combines a belt drive for the 20" floor auger and a direct-drive gearbox for the 22" vertical auger. The belt drive has two 4-strand belts and dual spring-loaded tensioners for easy maintenance. There's also a drivetrain disengagement lever for easy resetting if augers are accidentally engaged when full.



Model 1648



Hydraulic spout control for easier unloading and two auger-mounted lights automatically turn on when the unloading auger is extended for fully visible nighttime unloading.



WeatherGuard rolover tarp with semi-trailer design is constructed of 18-oz. canvas; bows are trussed and reinforced to prevent sagging.



The 12'4" x 3' tracked undercarriage features 40" idler wheels and 8 oscillating bogie wheels for optimum ground contact and a soft footprint. Hydraulic tensioning allows for easy maintenance, track alignment and weight distribution. There's also a debris cover for protecting track components.



Parker grain cart model 1648 specifications

Capacity*	1,600 bushels
Unloading speed	840 bu./min.
Approx. empty weight	28,935 lbs.
Approx. empty tongue weight	3,800 lbs.
Approx. loaded tongue weight	5,500 lbs.
Overall width	12'2"
Overall length	34'2"
Transport height	12'9"
Loading-side height	11'5"
Auger unloading height	15'5"
Auger reach	8'10"
Lift-auger tube diameter	22"
Floor-auger tube diameter	20"
Flighting	1/2" thick edge in high-wear areas; 3/8" leaned thick edge elsewhere
Track loaded ground pressure (P.S.I)	15

*Capacities measured with #2 corn at 15% moisture (56 lb. test weight)
 Due to continuing improvements in the design and manufacture of all Unverferth products, all specifications contained herein are subject to change without notice.

Options



Optional UHarvest™ data system provides full ISO terminal or tablet operation while it tracks, stores and sends detailed harvest information. Or choose the basic scale package for accurately storing load weights.



Camera package to monitor auger unloading from the tractor cab with available second rear-mounted camera for safer backing and road travel.

Unverferth
 Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853
 (419) 532-3121 • unverferth.com
1-800-322-6301

www.parkerequip.com

See your nearest Parker products dealer today for complete details about all the Parker grain carts, check our website at www.parkerequip.com or call 1-800-322-6301.



Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. We support the efforts of Farm Safety 4 Just Kids and all organizations that promote farm safety.



©2013 Unverferth Manufacturing Co., Inc. Printed in U.S.A.
 Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada

®™ Trademarks, registered or applied for, of Unverferth Mfg. Co., Inc., Kalida, Ohio
 PK16483162800M52