

# **TOP AIR® 3-POINT SPRAYERS**

*Top Air® 300-gallon 3-point sprayers provide exceptional maneuverability and unmatched performance for any size operation.*

**300 GALLON**





## 3-POINT SPRAYER FEATURES AND BENEFITS

- Equipped with a 300-gallon capacity tank, hydraulic pump and manual agitation control.
- Available with a 45' manual, 45' or 60' hydraulic cross-fold, self-leveling boom with three-section boom shutoff.
- Outer wing breakaway quickly returns to spraying position should it come into contact with an obstruction.
- Compact design and fold for narrow transport width and height, along with standard parking stands for easy storage.
- Slow moving vehicle sign and reflective striping for safer road travel.
- Optional fence-row nozzle kit for operator convenience.
- Nozzle spacing available in 15" or 20" to meet the needs of different operations.
- Hydraulic vertical height control on the 45' and 60' hydraulic cross-fold booms allows for easier spraying of taller crops.
- Frame and boom feature high-quality finish for enhanced corrosion resistance.
- Optional foam marker gives you precise spraying, pass after pass.

**Stop at your local Top Air dealer today or visit us online at [topairequip.com](http://topairequip.com) and check out the Top Air 3-point sprayer!**



**Unverferth**  
Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853  
419-532-3121 • [unverferth.com](http://unverferth.com)

As we continually strive to improve our products, all specifications contained herein are subject to change without notice or obligation.

## SPECIFICATIONS

	45' MANUAL-FOLD BOOM	45' HYDRAULIC CROSS-FOLD BOOM	60' HYDRAULIC CROSS-FOLD BOOM
Transport Height	7' 7"	10'	10'
Transport Width	8'	12'	13'
Length Added	6'	7' 7"	7' 7"



Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. We support the efforts of Farm Safety 4 Just Kids and all organizations that promote farm safety.



®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co. Inc., Kalida, O.H.

© 2016

TA3PT300611020M3