NEW MODEL LAUNCH

ALL-NEW XN-SERIES GRAIN CARTS

X-TREME® FRONT-FOLD, SINGLE-AUGER



NARROW-HOPPER, FRONT-FOLDING, SINGLE-AUGER GRAIN CARTS

EXTREME REACH WITH A NARROWER DESIGN.

The Unverferth X-Treme® grain cart has developed a solid reputation as being a reliable harvest partner with extreme auger reach and height to easily fill trucks. The all-new XN-Series builds on that reputation with a narrower hopper width designed to provide added versatility while maintaining the highest performance output. The XN-Series features a patented front-folding, single-auger design with a U-joint connection that angles the upper auger outward, forward and upward for maximum side reach, excellent operator visibility and the ability to clear tall trucks. Available with a traditional left-hand unloading auger or a right-hand unloading auger, the XN-Series offers unloading flexibility to match operator preference. A rear access door with an ergonomic ladder allows the user to easily enter the hopper for quick and complete cleanout. Models X1100N and X1000N feature capacities of 1100 and 1000 bushels and have a 12' wide hopper with paint options including tractor green, red or metallic gray for a high-quality, long-lasting finish.



INNOVATING THE FUTURE OF AGRICULTURE

GRAIN HANDLING

XN-SERIES MODELS

X-TREME GRAIN CART FEATURES

- Models X1100N and X1000N feature **hopper capacities** of 1,100 and 1,000 bushels with a 12' wide hopper and can be painted in tractor green, red or the all-new metallic gray.
- The hopper features a **deep sump** in the bottom to funnel grain down into the auger for maximum unloading efficiency and complete cleanout.
- Hydraulically operated **30" flow gate** with easy-to-view position indicator allows the operator to throttle the speed of the grain being unloaded.
- **Wheel operated door** in the bottom of the hopper for easy clean out or convenient pit dumping.
- The standard **hydraulic-powered auger rest stand** allows the operator to raise and lower the bracket from the tractor cab for convenient in-field or road transport storage of the upper auger.
- **Standard roll-tarp** on model X1100N protects the harvested crop and features gust straps that keep the tarp tight when rolling in windy conditions.
- 20" diameter auger unloads up to **650 bushels per minute**, and the Max-Edge 3/8" auger flighting has 1/4" AR400 material in high volume area for maximum life.
- The **unique front-folding design** folds the auger within the width of the grain cart for road transport, or the user can deploy the field rest stand to quickly return the auger to the unload position when operating in-field.
- **Patented auger design** features a flex-drive coupler for smooth engagement and a U-joint connection that angles the auger outward, forward and upward.
- Standard **four-way directional downspout** allows the operator to move grain in-and-out and side-to-side to easily top off trucks.
- The new XN-Series can be equipped with high flotation **single wheels and tires, 36" wide tracks,** or for the ultimate in flotation, the **42" wide Equalizer track** with side-to-side cambering to follow field contours and crowns in the road.
- **Options** for the X-Treme grain cart include a remote scale display that mounts into a recessed area in the side of the hopper, 410 or 520 scale displays, UHarvest Pro ISOBUS scale and data management system, water delivery system with 150-gallon tank, 4-function joystick controller and electric roll-tarp.

XN-SERIES SPECIFICATIONS		
MODEL	X1100N	X1000N
Capacity (bushels)	1,100	1,000
Engine HP	225	200
Loaded Tongue Weight (lbs.)	6,000	
Empty Tongue Weight (lbs.)	3,100	
Hydraulic Remotes Required	4	
Hopper Slope (front/rear)	33.5°/30°	
Hopper Length	21' 6"	
Hopper Width	11' 10"	
Auger Side Reach Max/Min	9' 5"/4' 9"	
Hitch to Spout (with spout straight down)	3'	
Overall Transport Length	26' 9"	
Hitch to Center of Axle	16' 5"	

TRACKED UNDERCARRIAGE	X1100N 42" x 131"	X1000N 36" x 112"
Approx. Empty Weight (lbs.)	24,000	19,000
Hitch Height	1' 7"	1' 6"/1' 9"
Hopper Height Low Side	11' 7"	11' 6"
Hopper Height High Side	12' 7"	12' 6"
Auger Height (with spout straight down)	12' 9"	12' 8"
Height to Top of Auger	17'	16' 11"
Width Outside of Tracks	12' 10"	11' 10"
Center of Track to Center of Track	9' 4"	9' 8"
Under Frame Clearance	1' 3"	1' 2"

Bushel capacities and unloading speeds are measured with #2 corn at 15% moisture (56 lb. test weight).
Due to continuing improvements in the design and manufacture of Unverferth Mfg. products, all specifications contained herein are subject to change without notice.


REAR ACCESS DOOR AND LADDER


LED INSET SCALE DISPLAY


NARROW HOPPER & EXTREME REACH

STREAMLINE YOUR GRAIN OPERATION.

Visit UMequip.com or see your nearest X-Treme grain cart dealer for more information.

For relevant patent marking, please visit unverferth.com/patents. Additional patent(s) may be pending.

Unverferth Manufacturing Company, Inc.

UNVERFERTH MFG. CO., INC.
P.O. BOX 357, KALIDA, OH 45853, USA • UNVERFERTH.COM • 800.419.4335

© 2026 Unverferth Manufacturing Co., Inc.
®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH
Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Texas, Washington and Ontario and Saskatchewan, Canada

UMXN2610MA1