



NEW FOR 2026
ALL-NEW X-SERIES
GRAIN CARTS
X-TREME® FRONT-FOLD, SINGLE-AUGER



FRONT-FOLDING, SINGLE-AUGER GRAIN CARTS
RE-DEFINING AUGER **REACH & HEIGHT**

The Unverferth X-Treme® grain cart has developed a solid reputation as being a reliable harvest partner with extreme auger reach and height to easily fill trucks. The all-new X-Series takes that reputation to new levels with increased auger reach and height, and a new right-hand unload option that takes your harvest efficiency to a whole new level. The X-Treme cart features a patented front-folding, single-auger design with a U-joint connection that angles the upper auger outward, forward and upward for maximum side reach, unparalleled operator visibility and clearing the tallest trucks. The new X-Series can be ordered with a traditional left-hand unloading auger, or with a right-hand unloading auger to match operator preference. The new rear access door with ergonomic ladder allows the user to easily enter inside the hopper for quick and complete cleanout. Capacities range from 1,550 to 1,100 bushels and can be painted in tractor green, red or the all-new metallic gray for the highest quality, long-lasting finish.



NEW X-SERIES FEATURES

- Increased auger side reach and height to easily reach over obstacles and clearing trucks with taller sides.
- Optional right-hand unload configuration is available in addition to the traditional left-hand unload auger.
- Rear access door with ergonomic ladder to easily access the inside of the hopper for quick and complete cleanout.
- Other new features include a metallic gray color option, improved hydraulic hose caddy, PTO holder for use during storage, gust straps for the tarp and recessed area for the remote scale display option.

INNOVATING
THE FUTURE OF
AGRICULTURE

GRAIN HANDLING

X-SERIES MODELS

X-TREME GRAIN CART FEATURES

- Models X1500, X1300 and X1100 **feature hopper** capacities of 1,550, 1,330 and 1,100 bushels and can be painted in tractor green, red or the all-new metallic gray.
- The hopper features a **deep sump** in the bottom to funnel grain down into the auger for maximum unloading efficiency and complete cleanout.
- Hydraulically operated **flow gate** with easy-to-view position indicator allows the operator to throttle the speed of the grain being unloaded.
- A wheel operated **cleanout door** in the bottom of the hopper allows the user to easily cleanout any remaining grain.
- **Standard roll-tarp** protects the harvested crop and features gust straps that keep the tarp tight when rolling in windy conditions.
- The 20" diameter auger unloads grain **up to 650 bushels per minute**, and the exclusively designed Max-Edge 3/8" auger flighting has 1/4" AR400 material added in high volume areas for maximum auger life.
- The **unique front-folding design** folds the auger within the width of the grain cart for road transport, or the user can deploy the field rest stand to quickly return the auger to the unload position when operating in-field.
- **Patented auger design** features a flex-drive coupler for smooth engagement and a U-joint connection that angles the auger outward, forward and upward.
- Standard **four-way directional downspout** allows the operator to move grain in-and-out and side-to-side to easily top off trucks.
- The new X-Series can be equipped with high flotation **single wheels and tires, 36" wide tracks**, or for the ultimate in flotation, the **42" wide Equalizer track** with side-to-side cambering to follow field contours and crowns in the road.
- **Options** for the X-Treme grain cart include a remote scale display that mounts into a recessed area in the side of the hopper, 410 or 520 scale displays, UHarvest Pro ISOBUS scale and data management system, water delivery system with 275-gallon tank, 4-function joystick controller and electric roll-tarp.

X-SERIES SPECIFICATIONS

MODEL	X1500	X1300	X1100
Capacity (bushels)	1,550	1,330	1,100
Engine HP	300	250	225
Loaded Tongue Weight (lbs.)	4,400		
Empty Tongue Weight (lbs.)	3,400		
Hydraulic Remotes Required	4		
Hopper Slope (front/rear)	32.5°/32°		
Hopper Length	25' 4"		24' 9"
Hopper Width	13' 8"		
Auger Side Reach Max/Min	10' 5"/9'		
Hitch to Spout (with spout straight down)	2' 10"		
Overall Transport Length	31' 4"		30' 10"
Hitch to Center of Axle	18' 10"		

TRACKED UNDERCARRIAGE	X1500 42" x 148"	X1300 42" x 131"	X1100 42" x 131"
Approx. Empty Weight (lbs.)	30,400	27,600	27,300
Hitch Height	1' 10"	1' 9"	
Hopper Height Low Side	12'	11' 3"	10' 7"
Hopper Height High Side	13'	12' 3"	11' 7"
Auger Height (with spout straight down)	13' 5"	13' 4"	
Height to Top of Auger	17' 9"	17' 8"	
Width Outside of Tracks	13' 11"		
Center of Track to Center of Track	10' 5"		
Under Frame Clearance	13"	12"	

Bushel capacities and unloading speeds are measured with #2 corn at 15% moisture (56 lb. test weight).

Due to continuing improvements in the design and manufacture of Unverferth Mfg. products, all specifications contained herein are subject to change without notice.



REAR ACCESS DOOR AND LADDER



LED INSET SCALE DISPLAY



U-JOINT CONNECTION

STREAMLINE YOUR GRAIN OPERATION.

➔ Visit **UMequip.com** or see your nearest X-Treme grain cart dealer for more information.

Unverferth
Manufacturing Company, Inc.

UNVERFERTH MFG. CO., INC.
P.O. BOX 357, KALIDA, OH 45853, USA • UNVERFERTH.COM • 419.532.3121

© 2025 Unverferth Manufacturing Co., Inc.
®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH
Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Texas, Washington and Ontario and Saskatchewan, Canada