



# New!

## Introducing **MODEL 2520**

20-SERIES GRAIN CART  
FOR MODEL YEAR 2025



### DUAL-AUGER HARVESTING POWER IN 2,500-BUSHEL CAPACITY

Your time is money, which is why we've designed the new Unverferth 2,500-bushel capacity, dual-auger model 2520 grain cart to be one of the largest, fastest and most efficient grain carts on the market. Get exceptional unloading power and speed from the proven combination of horizontal and vertical augers, plus a variety of innovative features that simplify your hands-on tasks to let you focus on the bigger picture. The 2520 features a pivoting unloading auger and an adjustable directional downspout for precisely filling grain trailers at up to 1,000 bushels per minute. Add in the standard rubber-cushioned tongue suspension, rear tank access door with ergonomic ladder, hydraulic jack, 520 scale and Equalizer® track, and you've got one of the most powerful and feature-rich grain carts on the market today.

### LARGER CAPACITY WITH POWERFUL UNLOADING

The drivetrain features P.T.O. with cut-out clutch powering a 90-degree gearbox for the 24" diameter vertical auger and dual belt-driven 20" diameter horizontal auger for worry-free use and fast unloading speeds up to 1,000 bushels per minute to quickly return to the combine. The augers are constructed with 3/8" flighting with 1/4" abrasion-resistant strips added in high-wear areas and computer balancing for long-term performance. The soft-start auger connection provides smooth engagement of the upper and lower vertical augers for less driveline stress. The dual-auger design features steep sloped tank sidewalls that ensure complete cleanout during every unload, even in high-moisture grain. This design also provides a narrower transport width for safer road travel and a lower tank profile for easier filling and greater stability on sidehills.

KEY FEATURES



**CAPACITY**  
2,500 BUSHEL



**UNLOADING**  
1,000 BUSHEL/MINUTE



**AUGER DESIGN**  
PIVOTING VERTICAL



**UNDERCARRIAGE**  
2 TRACK OPTIONS

## GRAIN HANDLING

**INNOVATING  
THE FUTURE OF  
AGRICULTURE**

**20-SERIES MODEL 2520  
UMEQUIP.COM**

# OPTIONS & ACCESSORIES

## UNDERCARRIAGE OPTIONS

Choose from two tracked undercarriage designs that feature exclusive 50"-wide single-piece molded rubber belts for unmatched longevity. For maximum flotation, the 50"-wide Equalizer SP track system provides 128" of ground contact length and features patented 4-way oscillation so the bogies can pivot up and down and left and right to keep the entire footprint of the belt in firm contact with the ground. The 50"-wide Equalizer track provides 105" of ground contact length and features side-to-side cambering. Both track systems include an auto-greaser for regular lubrication of pivoting points.



50" Equalizer SP track system

## SCALE OPTIONS

All 2520 grain carts are standard with a model 520 scale package that features auto-log for automatically recording each load. The optional UHarvest® Pro data management system takes harvest management to the next level with touch screen operation from your tractor's ISOBUS display and automatically recording each load with grower/farm/field/truck and crop information for detailed harvest reporting. UHarvest Pro "Connections" allows you to sync your grower, farm and field information from the John Deere Operations Center™ with the touch of a button.



520 scale package

## ACCESSORIES

Choose from a wide range of options and accessories to equip your new 2520 grain cart exactly how you want it. The 5-function joystick controller option allows the operator to control all functions of the grain cart from a convenient handheld pistol grip remote. The water delivery system features a custom 275-gallon tank, Ace 204 hydraulic pump, 100' of hose and firehose-style nozzle. Other options include a rear hitch with 20,000-pound capacity, remote scale display mounted on the side of the grain cart, electric roll tarp operation and color cameras.



Water delivery system

Model 2520															
Track Undercarriage	Capacity*	Min. H.P.	Loaded Tongue Weight	Augers (Vertical/Horizontal)	Unload Speed	Auger Flighting	Hopper Length	Hopper Width	Auger Side Reach Max.	Transport Length	Empty Weight	Hopper Height Low Side	Hopper Height High Side	Auger Height	Overall Width
50" x 148" Equalizer	2,500 bushels	4WD-500+	6,700 lbs.	24"/20"	1,000 bu./min.	3/8" with 1/4" AR400	33'	13' 10"	8' 2"	42' 6"	37,680 lbs.	11' 5"	12' 5"	14' 8" to 10' 7"	13' 11"
50" x 172" Equalizer											41,060 lbs.				

\*Bushel capacities and unloading speeds are measured with #2 corn at 15% moisture (56-pound test weight).

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice. For relevant patent marking, please visit [Unverferth.com/patents](http://Unverferth.com/patents).

STREAMLINE YOUR HARVEST OPERATION → visit [UMequip.com](http://UMequip.com) or see your nearest dealer today.



**Unverferth**  
Manufacturing Company, Inc.

UNVERFERTH MFG. CO., INC.  
P.O. BOX 357, KALIDA, OH 45853, USA • [UNVERFERTH.COM](http://UNVERFERTH.COM) • 419.532.3121

© 2024 Unverferth Manufacturing Co., Inc.  
®, ™ Trademarks, registered or applied for, of their respective owners.  
Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Texas, Washington, and Ontario and Saskatchewan, Canada