

The conditioning choice for more than 25 Years

When it comes to soil conditioning, nothing outperforms the Unverferth Rolling Harrow[®] soil conditioner. It's the one that has become synonymous with the ultimate in seedbed finishing. For soils that need only a lighter finishing touch, look to the pull-type model 165 single basket Rolling Harrow soil conditioner. The scalloped blades, combined with the aggressively designed leading angle of the roller, ensure maximum soil penetration and mixing.

Working widths from 12' to 50'

Unverferth[®] Tillage

Single Basket Rolling Harrow® Model 165 soil conditioner for lighter soils

- Large-diameter 16" baskets with ten ¾"-thick high-carbon steel blades, and 2¾"- steel-center shaft with reinforcing discs spaced every 10" to 12" for optimum performance
- Baskets are reversible for either aggressive mixing or more passive surface firming
- 4-bolt flanged bearings feature triple-lip seals for maximum life
- Superior clearance between the roller and roller frame ensures uninterrupted operation
- Complete with hydraulic hoses with protective end caps; single-hose sets on 12'-36' models, two-hose sets on 38'-50' models; kits available for converting single sets to doubles and doubles to singles
- Horsepower requirement is ½ hp to 1 hp per foot of operating width
- Large-diameter dual-transport wheels are positioned ahead of the roller for eliminating tracks and enhanced in-field stability; 3-section models have
 7.60 x 15 tires and 5-section models are equipped with 9.50 x 15 tires
- Models from 38' to 50' feature mid-wing mounted 9.50 x 15 wheels/tires for added in-field stability; all models available with optional 9.50 x 15 wingmounted list-assist wheels
- Extendible tongue length for added turning clearance
- · Available with straight spike-tooth, diagonal round-tooth or coil-tine leveling bars
- Optional lighting package for enhanced transport visability



Rolling Harrow [®] Model 165 — Vertical Folding						
Models with 12' Base — 50-12 ft. Widths						
Working Width	Transport		Width		Fold	Approx. Weight (lbs.)
	Width	Height	Base	Wings, Ea.	FUIU	with Harrow
50'	15' 7"	14'	12'	19'	5-Section	7,600
48'	15' 7"	14'	12'	18'	5-Section	7,545
46'	15' 7"	14'	12'	17'	5-Section	7,485
44'	15' 7"	14'	12'	16'	5-Section	7,425
42'	15' 7"	14'	12'	15'	5-Section	7.365
40'	15' 7"	14'	12'	14'	5-Section	7,305
38'	15' 7"	14'	12'	13'	5-Section	7,265
36'	15' 7"	15' 9"	12'	12'	3-Section	6.865
34'	15' 7"	14' 9"	12'	11'	3-Section	6,785
32'	15' 7"	13' 9"	12'	10'	3-Section	6.000
30'	15' 7"	12' 9"	12'	9'	3-Section	5.800
28'	15' 7"	11'9"	12'	8'	3-Section	5,500
26'	15' 7"	10' 9"	12'	7'	3-Section	5.200
24'	15' 7"	9' 9"	12'	6'	3-Section	4,850
12'	12'	-	12'	-	-	2,900

For complete details on the Unverferth Rolling Harrow soil conditioner and all Unverferth tillage tools, see your nearest Unverferth dealer today, check our Web site at www.unverferth.com or call 1-800-322-6301.

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



Manufacturing Company, Inc. P.O. Box 357 • Kalida, Ohio 45853 (419) 532-3121 • FAX (419) 532-2468 unverferth.com

1-800-322-6301

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2010 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

® ™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada

