

**Unverferth**® Tillage

*Rolling Reel Leveler Model 75*



## **Primary tillage partner** *for smooth secondary tillage*

*The Unverferth Rolling Reel Leveler is the ideal soil-finishing partner to pull behind your primary tillage tool. Its 16" diameter chopping reels feature five spiraled, 3/8" x 3" beveled-edge blades for breaking up clods, knocking dirt off rootballs, smoothing residue and leveling ridges for a more receptive spring tillage trip. Save time, fuel and engine hours for lowering your input costs.*

*15' and 18' rigid models; 18', 20', 22', 25' folding models*



## Rolling Reel Leveler primary tillage partner for a more receptive spring tillage trip

- Available in 15' and 18' rigid and 18', 20', 22' and 25' folding models
- 16" diameter chopping reels with five, 3/8" x 3" beveled-edge blades for ideal leveling and better cleanout in heavier soils or wetter conditions
- Spiraled-blade design keeps blades in contact with soil surface for optimum leveling with minimal vibration
- Rugged 4" x 6" main frame and wing construction for added life
- Heavy-duty, 4-bolt flange bearing with 1 3/4" diameter shaft for long-term dependability
- 4" x 4" telescoping tongue retracts for easier storage and easy attachment to the lead implement
- Height-adjustable, reversible single-tang double-clevis hitch for easy hitching to lead tool
- Top-winding, drop-leg jack for easy parking and a secondary position for in-field use
- 3,000 p.s.i. hydraulics complete with hoses and endcaps for keeping hydraulic fluid cleaner
- Single hydraulics standard on folding models; dual hydraulics optional
- Standard 9.5 x 15 transport wheels and available dual wheel option
- SMV emblem, reflective markers and safety chain are standard equipment for enhanced transport safety
- Optional lighting package provides additional visibility for safer road travel
- Available in powder-coat finish of tractor red or green
- Horsepower requirements of 1 to 1 1/2 per working foot
- Optional wing-fold lockout valve for use with single hydraulics that allows wings to remain unfolded when turning



Rigid and folding models



Drop-leg jack for easy parking and storage



4-bolt flange bearing with 1 3/4" shaft for durability

For complete details on the Unverferth Rolling Level soil conditioner and all Unverferth tillage tools, see your nearest Unverferth dealer today, check our website at [www.unverferth.com](http://www.unverferth.com) or call 1-800-322-6301.

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



**Manufacturing Company, Inc.**  
P.O. Box 357 • Kalida, Ohio 45853  
(419) 532-3121 • FAX (419) 532-2468  
[unverferth.com](http://unverferth.com)  
**1-800-322-6301**

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2010 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH  
Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada



URR0151200M5