



Finish What You Start

Tillage Extras From The High ***IQ**** Line



Innovative design • ***Q***uality manufacturing



Finish What You Start

Tillage Extras From The High IQ* Line

Finish what you start has always been good advice; especially when it comes to seedbed preparation. From smoothing and firming the soil behind a drill for better seed-to-soil contact, to knocking down ridges and breaking up clods behind a primary tillage implement, only Unverferth offers the variety of tillage extras you need for putting the finishing touches to any tillage or planting operation.

Rolling Harrow® Baskets

Mount them to a disc harrow, field cultivator, drill or other secondary tillage implement and you'll find Unverferth Rolling Harrow® Basket attachments superior to rollers with straight blades or round bars for soil conditioning and residue and chemical incorporation.

The leveling bar, which can be equipped with your choice

of spike-tooth, coil-tine or diagonal round-tooth, knocks down ridges and smoothes the surface for the most effective residue and chemical incorporation.

The aggressive, field-proven 12-inch diameter baskets feature eight, scalloped and angled high-carbon steel blades and a 1-inch solid-steel center shaft for long-term performance, even in the rockiest conditions. Bearings with triple-lip seals provide long life and minimal maintenance.

Double Rolling Harrow® Baskets

The Double Rolling Harrow Basket attachment features an aggressively designed lead roller with serrated edges and pitched blades that chew up clods and mix the soil. The more passive trailing roller firms and finishes the soil. The result is a smooth, level seedbed with coarser soil on the surface to resist crusting and finer soil at planting depth for optimum seed-to-soil contact. That means enhanced germination and more uniform emergence.

Two universal mounting arms per section are easily attached to 3" x 4" through 6" x 6" toolbars for consistent and uniform downpressure and the 12-inch diameter baskets are available in 3', 4' and 5' widths.

Double Rolling Harrow
Basket attachment



Single Rolling Harrow Basket
with extended-length arms



Single Rolling Harrow Basket



Single Rolling Harrow® Baskets

The Single Rolling Harrow Basket attachment also features the 12-inch diameter aggressive roller and leveler bar. Its two universal mounting arms per section will mount onto 3" x 3" through 6" x 6" toolbars.

You'll need the Single Rolling Harrow Basket attachment with extended-length arms for C-shank field cultivators and other applications requiring additional clearance. Its two universal mounting arms adapt to 3" x 3" through 6" x 6" toolbars and provide 34 inches of clearance between the toolbar and the leveler bar.

Powder-coated painting assures a long-lasting finish to all Rolling Harrow Basket models.

Single Rolling Harrow Baskets For Drills

Whether no-till or conventional till, adding the Single Rolling Harrow Basket attachment to a grain drill helps chop and distribute residue and firm and level the soil for better seed-to-soil contact and more uniform germination.

The baskets can be reversed for additional soil firming, and the spring-controlled downpressure is easily adjusted for uniform and consistent operation. They can be raised and lowered with the drill, or if desired, raised into a non-use position and still plant.

The Single Rolling Harrow Basket attachment is available in 15- and 20-foot widths and can be fitted to selected John Deere, Case IH, Great Plains and Tye drills.



Single Rolling Harrow
Baskets for Grain Drills

S-Tine Leveler

For those who prefer a one-pass chisel plant operation, the S-Tine leveler and optional One-Bar Harogator® leveler add the finishing touches needed for optimum soil leveling and residue incorporation.

There's a hefty 23 inches of underside clearance beneath the heavy-duty 5/16" x 1 3/4" S-Tines with 7-inch sweeps, and the 3" x 3" heavy-wall toolbar provides an abundance of operational strength. Residue flow is easily regulated by simple pin settings for adjusting the angle of the mounting arms. Powder-coated painting assures a durable finish.

Universal mounting arms are angle adjustable and fit toolbars up to 7" x 7". S-Tine levelers are available in models to fit 8' to 28' chisel plows.



S-Tine
leveler

One-Bar Harogator Leveler

Whether attached to the S-Tine leveler, or hooked directly to the rear of the implement, the One-Bar Mounted Harogator leveler is the ideal economical leveling attachment for many tillage applications.

It can mount to any 3" x 3" through 6" x 6" toolbar and is available in 3' to 9' sections. The spring-tension adjustment for each arm is easily set. Left-hand and right-hand designs provide symmetrical mounting and leveling action, and the center Y-tooth ensures complete smoothing of the center.

Outstanding durability is the result of powder-coated painting, heat-tempered teeth, and the "kick-back" hinged leveling bar that protects against damage from rocks and other field obstacles or when the implement is being backed or lowered.



One-Bar Harogator
leveler

See Your Unverferth Dealer

Simply put, nobody has more soil conditioning and finishing options than Unverferth. And no one is better equipped to help you choose the right ones for your operation than your Unverferth dealer. Stop by and see for yourself. There's no better way to finish what you start.



Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853
(419) 532-3121 • FAX (419) 532-2468
unverferth.com

1-800-322-6301

©2006 Unverferth Manufacturing Co., Inc.
Printed in U.S.A.



Please remind all family members to use caution and follow recommended safety practices when around all farm equipment. Unverferth Mfg. Co., Inc. supports the efforts of Farm Safety 4 Just Kids



®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH
Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada

TA60025160M10