



# UNVERFERTH® IMPLEMENT CADDY



**MODEL 700**



**MODEL 500**

## **PUT ALL YOUR HORSEPOWER TO WORK!**

Put all your big-tractor horsepower to work with the **Unverferth implement caddy**. The 3-point quick-hitch connection and exceptional lift capacity make one-person hookup to virtually all 3-point equipment fast, simple and straightforward.

**TILLAGE**

MODELS 700  
AND 500  
**UMEQUIP.COM**

# UNVERFERTH®

## TILLAGE

### Put All Your Horsepower to Work

Big-tractor horsepower doesn't do you any good if it can't be used for all your tillage needs. The Unverferth® implement caddy features easy hookup to virtually all 3-point equipment, including the Zone-Builder®, Ripper-Stripper®, Ripper-Roller and Ripper-Bedder subsoilers, and their mounted tillage attachments.

- Dual wheels for greater flotation and transport stability
  - Adjustable tongue height with single-tang hitch for easily matching the tractor drawbar
  - Standard transport chain
  - Adjustable top link for easily leveling the attached implement
  - 3,000 psi hydraulic cylinders for quickly raising and lowering unit
  - Choice of powder-coat tractor-red or green finish for optimum corrosion resistance
  - Standard rear-mounted electrical connection for easily connecting transport lighting
  - Rear hydraulic remote connection standard on model 700; optional on model 500
- **The model 700 fits up to 16-shank rippers and features:**
    - Parallel axle lift arms for level, uniform lifting with up to 30" of clearance
    - 8" x 8" tubular steel axle arms for enhanced durability
    - Available with Cat. 4 narrow-hitch attachment
    - Pull-through 4" x 10" steel frame
    - Oscillating dual wheels for enhanced transport stability
  - **The model 500 fits up to 9-shank folding machines**
    - Pull-through design with a fully welded 4" x 8" tubular steel frame for maximum strength
    - Cat. 3 lower quick-hitch with auto-latch attachment; top quick link standard
    - Durable 6" x 6" tubular steel axle arms
    - Up to 34" of transport clearance

#### Specifications

Model	Dual Tire Size	Fits Machine	Lift Capacity	Width	Length	Max. H.P.
Model 700	385/65 x 22.5 163D LI	Up to 16 shanks	22,000 lbs.	14'1"	19'10"	600
	295/75 x 22.5		16,000 lbs.			
Model 500	14L x 16.1 14-Ply	Up to 9 shanks	13,000 lbs.	10'7"	13'8"	500
	IF320/70R x 15					

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice. For relevant patent marking, please visit [unverferth.com/patents](http://unverferth.com/patents).

**TO LEARN MORE ABOUT THE UNVERFERTH IMPLEMENT CADDY,**  
 —> visit your nearest Unverferth dealer or [UMequip.com](http://UMequip.com) for details

**Unverferth**  
 Manufacturing Company, Inc.



UNVERFERTH MFG. CO., INC.  
 P.O. BOX 357 KALIDA, OH 45853 • UNVERFERTH.COM • 419.532.3121

© 2023 Unverferth Manufacturing Co., Inc. Printed in U.S.A.  
 ®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH  
 Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon, Texas and  
 Ontario and Saskatchewan, Canada

CADDY32512005M1