

Unverferth® Tillage

Freedom® 3-point tillage attachments



Freedom® 3-point implements *for utility tractors*

Freedom 3-point hitch implements for utility tractors are ideal for soil and seedbed preparation tasks around farmsteads, feedlots, commercial buildings, golf courses and parks. They're equally well-suited for new construction or landscape renovation.

Soil ripper, Disk, Land leveler

3-point implements for utility tractors

All Freedom® 3-point implements for utility tractors are constructed with the highest quality craftsmanship and materials for long-term dependability. Powder-coat finishes in your choice of tractor red, green, blue or orange resist corrosion and keep the implements looking as professional as your finished work.

Soil Ripper — Breaks up tightly compacted soil to allow better drainage and plant roots to move freely into the subsoil for enhanced growth.

- Special-alloy steel, $\frac{3}{4}$ " -thick angled shanks
- Easy-to-replace raised points
- Available wearbar kit for longer life
- Operating depth up to 18 inches
- Shear bolt-protected
- 4" x 4" steel tube frame with parking stands
- Available in 1-shank model with combination category I/II hitch
- 2-shank models with category II hitch
- Horsepower requirement of 25-35 hp per shank



Tandem Disk — When surface conditions are so tough that only a disk can get it back into shape for final finishing

- Both front and rear gangs, or either, can be fitted with 18"-notched blades for aggressive penetration and tillage, or 18"-conventional blades for finishing, smoothing and firming
- 1 $\frac{1}{8}$ " gang bolts
- 7 $\frac{1}{2}$ " disc blade spacing with offset gangs for effective cutting every 3 $\frac{3}{4}$ "
- Cutting angle of front gangs can be set to 0°, 7°, 14°, 18° or 21°
- 2 $\frac{1}{2}$ " -square steel tube frame and 3" x 2" disc gang tube frames
- Category 1 hitch
- Available working widths of 5 $\frac{1}{2}$ ' and 6 $\frac{1}{2}$ '
- Optional leveling rake, soil finishing basket, weight tray and blade scrapers
- Horsepower requirement of 5 to 6 hp per foot of width



Land Leveler — Smooths, pulverizes and levels the soil surface to create the most receptive seedbed possible. Also works well for grooming driveways, pathways and athletic fields.

- Steel tube frame with welded-steel construction
- Cross-bracing for added durability
- Front blade knocks down ridges and channels material to rear
- Rear angles spread materials out
- Rear blade fills and smooths the surface
- Replaceable wear blade option for greater durability
- Category I hitch
- 6' working width



For complete details on all the Freedom 3-point hitch implements for utility tractors, see your nearest Unverferth dealer today, check our website at www.unverferth.com or call 1.800.322.6301.

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



Manufacturing Company, Inc.
P.O. Box 357 • Kalida, Ohio 45853
(419) 532-3121 • FAX (419) 532-2468
unverferth.com

1-800-322-6301

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2011 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH
Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada



3pt1110900M5